

## SPECIFICATIONS

| Model                            |                    |            | CTI-130                        |
|----------------------------------|--------------------|------------|--------------------------------|
| Power Supply                     |                    | Ph-V-Hz    | 1P/220-240V/50                 |
| Cooling                          | Capacity           | W          | 14000<br>(5600-16800)          |
|                                  | Input              | W          | 4250<br>(1700-5100)            |
|                                  | Rated Current      | A          | 20.0 (8.0~24.0)                |
| Heating                          | Capacity           | W          | 14500<br>(5800-17500)          |
|                                  | Input              | W          | 4300<br>(1720-4750)            |
|                                  | Rated Current      | A          | 20.0 (8.0~24.0)                |
| Max. Input Consumption           |                    | W          | 5500                           |
| Max Current                      |                    | A          | 26.0                           |
| Compressor                       |                    | Type/Brand | Scroll / Toshiba               |
|                                  |                    | Btu/h      | 46750                          |
| Indoor Air Flow (Hi / Med / Low) |                    | m3/h       | 2300 / 2000 / 1800             |
| Indoor unit: Body                | Dimensions (WxDxH) | mm         | 840 x 840 x 287                |
|                                  | Packaging (WxDxH)  | mm         | 900 x 900 x 320                |
|                                  | Net/Gross weight   | KG         | 28.7 / 32.8<br>6.5/8.0 (panel) |
| Indoor unit: Pannel              | Dimensions (WxDxH) | mm         | 950 x 950 x 55                 |
|                                  | Packaging (WxDxH)  | mm         | 1035 x 1035 x 90               |
| Outdoor unit                     | Dimensions (WxDxH) | mm         | 952 x 415 x 1333               |
|                                  | Packaging (WxDxH)  | mm         | 1095 x 495 x 1480              |
|                                  | Net/Gross weight   | KG         | 116 / 130                      |

|                                    |                        |              |                            |
|------------------------------------|------------------------|--------------|----------------------------|
| Indoor unit: Pannel                | Dimensions (WxDxH)     | mm           | 950 x 950 x 55             |
|                                    | Packaging (WxDxH)      | mm           | 1035 x 1035 x 90           |
| Outdoor unit                       | Dimensions (WxDxH)     | mm           | 952 x 415 x 1333           |
|                                    | Packaging (WxDxH)      | mm           | 1095 x 495 x 1480          |
|                                    | Net/Gross weight       | KG           | 116 / 130                  |
| Refrigerant                        |                        | Type/g       | R410A/4600                 |
| Refrigerant Piping                 | Liquid Side / Gas Side | mm           | 9.52 / 19<br>(3/8" / 3/4") |
|                                    | Max. Pipe Length       | m            | 65                         |
|                                    | Max. Difference Level  | m            | 30                         |
| Operation temp (Cooling / Heating) |                        | C            | >16 / <31                  |
| Ambient temp (Cooling / Heating)   |                        | C            | -15 ~ 50 / -15 ~ 24        |
| Outdoor Noise Level                |                        | dB(A) (1.0m) | 62                         |
| Star rating (Cooling / Heating)    |                        | Stars        | 2.0 / 2.0                  |