

SPECIFICATIONS

Model		DSI-140	
Power Supply		Ph-V-Hz	1P/220-240V/50
Cooling	Capacity	W	14000 (5600-16100)
	Input	W	4250 (1290-4250)
	Rated Current	A	19.5 (5.8 ~ 21.7)
Heating	Capacity	W	14500 (5800~17500)
	Input	W	4300 (1700~5200)
	Rated Current	A	19.5 (7.8 ~ 23.5)
Max. Input Consumption		W	5500
Max Current		A	26.0
Compressor		Type / Brand	Scroll / Toshiba
		Capacity (Btu/h)	46750
Indoor Air Flow (Hi / Med / Low)		m3/h	3300 / 2850 / 2350
Indoor unit	Dimensions (WxDxH)	mm	1200 x 625 x 380
	Packaging (WxDxH)	mm	1485 x 675 x 450
	Net/Gross weight	KG	54.0 / 60.0
Outdoor unit	Dimensions (WxDxH)	mm	952 x 415 x 1333
	Packaging (WxDxH)	mm	1095 x 495 x 1480
	Net/Gross weight	KG	116 / 130

Refrigerant		Type/g	R410A/4600
Refrigerant Piping	Liquid Side / Gas Side	mm	9.52 / 19 (3/8" / 3/4")
	Max. Pipe Length	m	65
	Max. Difference Level	m	30
Operation temp (Cooling / Heating)		C	>16 / <31
Ambient temp (Cooling / Heating)		C	-15 ~ 50 / -15 ~ 24
Outdoor Noise Level		dB(A) (1.0m)	62
Star rating (Cooling / Heating)		Stars	2.0 / 2.0