

SPECIFICATIONS

Model		DSI-170	
Power Supply		Ph-V-Hz	1P/220-240V/50
Cooling	Capacity	W	17000 (6800-19500)
	Input	W	5155 (1560-5950)
	Rated Current	A	23.7 (7.0 ~ 26.5)
Heating	Capacity	W	17500 (7000~21000)
	Input	W	5200 (2050~6250)
	Rated Current	A	23.7 (9.5~28.5)
Max. Input Consumption		W	6000
Max Current		A	30.0
Compressor		Type / Brand	Scroll / Toshiba
		Capacity (Btu/h)	46750
Indoor Air Flow (Hi / Med / Low)		m3/h	3800 / 3200 / 2950
Indoor unit	Dimensions (WxDxH)	mm	1400 x 858 x 440
	Packaging (WxDxH)	mm	1605 x 910 x 505
	Net/Gross weight	KG	75.0 / 83.0
Outdoor unit	Dimensions (WxDxH)	mm	952 x 415 x 1333
	Packaging (WxDxH)	mm	1095 x 495 x 1480
	Net/Gross weight	KG	116 / 130
Refrigerant		Type/g	R410A/5600

Refrigerant Piping	Liquid Side / Gas Side	mm	9.52 / 19 (3/8" / 3/4")
	Max. Pipe Length	m	65
	Max. Difference Level	m	30
Operation temp (Cooling / Heating)		C	17 ~ 32 / 0 ~ 30
Ambient temp (Cooling / Heating)		C	-15 ~ 50 / -15 ~ 24
Outdoor Noise Level		dB(A) (1.0m)	62
Star rating (Cooling / Heating)		Stars	2.0 / 2.0