

Domain model			ISR-26H	ISR-35H	ISR-50H	ISR-70H	ISR78H
Cooling	Capacity	W	2500(1000~3100)	3500(1050~3700)	5000(1800~5700)	7000(2000~8000)	7800(2200~8800)
	Input	W	590(290~1300)	870(290~1150)	1510(300~2300)	2050(400~2800)	2340(540~3100)
	Rated Current	A	3.6(1.3~6.5)	3.8(1.3~5.3)	6.6(1.4~10.3)	8.9(1.9~13.5)	10.2(2.6~14.9)
	EER	W/W	4.43	4.10	3.28	3.42	3.31
Heating	Capacity	W	2500(1000~3700)	3500(1050~4500)	5000(1800~6500)	7000(2000~8500)	8000(2400~9000)
	Input	W	590(290~1500)	850(290~1400)	1420(300~2450)	1950(350~2900)	2350(640~3650)
	Rated Current	A	3.6(1.3~7.0)	3.7(1.3~7.6)	6.2(1.4~10.9)	8.5(1.7~14.5)	10.3(3.1~17.6)
	COP	W/W	4.33	4.19	3.54	3.58	3.39
Moisture Removal		L/H	0.8	1.1	2.0	2.4	2.8
Max. Input Consumption		W	1500	1400	2450	2900	3650
Max Current		A	9.0	9.5	13.5	15.0	16.0
Compressor	Type		Rotary	Rotary	Rotary	Rotary	Rotary
	Brand		Rechi	Panasonic	Rechi	Sanyo	Hitachi
Indoor Air Flow (Hi) (Cooling / Heating)		m3/h	550/550	900/930	900/930	1330/1430	1330/1430
*Indoor Noise Level (Low to High)		db(A)	24-42	28-45	28-46	32-52	32-52
Indoor unit	Dimensions (WxHxD)	mm	814×306×210	972×310×225	972×310×225	1095×327×235	1095×327×235
	Packaging (WxHxD)	mm	885×366×278	1036×371×295	1036×371×295	1158×388×308	1158×388×308
	Net/Gross weight	KG	9 / 11	12 / 15	12 / 15	15 / 18	15 / 18
Outdoor unit	Dimensions (WxHxD)	mm	760 x 551 x 256	760 x 551 x 256	780 x 605 x 290	900 x 805 x 360	900 x 805 x 360
	Packaging (WxHxD)	mm	863 x 600 x 325	863 x 600 x 325	883 x 653 x 412	1031 x 925 x 447	1031 x 925 x 447
	Net/Gross weight	KG	28 / 31	29 / 32	36 / 39	60 / 64	64 / 68
Refrigerant		Type/g	R410A / 1000	R410A / 1080	R410A / 1200	R410A / 2000	R410A / 2650
Refrigerant Piping		inch	1/4" & 3/8"	1/4" & 3/8"	1/4" & 1/2"	1/4" & 5/8"	3/8" & 5/8"
Operation temp		C	16~31	16~31	16~31	16~31	16~31
Ambient temp (Cooling / Heating)		C	-7 to 52 / -15 to 24	-7 to 52 / -15 to 24	-7 to 52 / -15 to 24	-7 to 52 / -15 to 24	-7 to 52 / -15 to 24
Applicable area		m2	10 - 22	18 - 32	28 - 47	40 - 67	48 - 75
Star rating (Cooling / Heating)		Stars	4.0 / 4.0	3.5 / 3.5	2.0 / 2.5	2.0 / 2.5	2.0 /2.0
Power Connection			Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Interconnecting Cable (Size / Cores)			1.5 / 5	1.5 / 5	2.5 / 5	2.5 / 5	2.5 / 5